

Thermal Transfer Ribbon

MATERIAL

DESCRIPTION: This high temperature black resin thermal transfer ribbon is suitable for use on specific high durability polyesters 704 & 708.

RIBBON TYPE: High Performance Thermal Transfer Resin

APPLICABLE PRINTERS: Sato/Zebra

APPLICABLE PRODUCTS: EE01QL181IPG

SHELF LIFE: 24 months stored 21°C (70°F) @ 50% RH

COLOR: Black

PRINT PERFORMANCE:

Test Description	Test Conditions	Contrast Score	
		Silver Label	White Label
Mark Adherence MIL-81531	50 rubs	Pass C10	Pass C10
IPA/M. Spirits MIL-202F	9 minutes immersion 30 strokes	Pass C10	Pass C10
BIOACT MIL-202F	9 minutes immersion 30 strokes	Pass C10	Pass C10
IPA Wipe	30 wipes	Pass C10	Pass C10
Paint Stripper Wipe	10 wipes	Pass C10	Pass C10
JP8 MIL-81531	24hr immersion at 23°C 20 wipes with rubber	Pass C9	Pass C8
H5606 MIL-81531	24hr immersion at 23°C 20 wipes with rubber	Pass C9	Pass C9
SKYDROL MIL-81531	24hr immersion at 23°C 20 wipes with rubber	Pass C9	Pass C9
Dry Taber	500 cycles 500gms	Fail C2	Pass C4

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Link Hamson makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Link Hamsons only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Link Hamson be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Link Hamson Specifications are subject to change without notice. In addition Link Hamson reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

181_05_08

