

# TECHNICAL DATA SHEET

## LP5113/\* (all variants) Thermal Transfer Ribbon

### MATERIAL

**DESCRIPTION:** This ultra solvent resistant black resin thermal transfer ribbon is suitable for use on Polyester label materials and provides excellent solvent resistance to chemicals commonly used in electronics manufacturing.

**RIBBON TYPE:** Resin

**APPLICABLE PRINTERS:** Sato/Zebra

**APPLICABLE PRODUCTS:** 711 (WP), 707 (MP)

**APPROVALS:** CSA listed for use with our 711/707 materials  
CSA Standard class 7924-01, file 099214\_L\_000  
(Adhesive-type-labels, Electronic Printing Technologies)

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Link Hamson makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Link Hamsons only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Link Hamson be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Link Hamson Specifications are subject to change without notice. In addition Link Hamson reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.

01/2009



LINK HAMSON LTD 6, YORK WAY, LANCASTER ROAD, CRESSEX BUSINESS PARK  
HIGH WYCOMBE, BUCKS, HP12 3PY, ENGLAND. TEL: +44(0)1494 439786 FAX: +44(0)1494 526222  
Please visit our website at [www.linkhamson.com](http://www.linkhamson.com) or contact us via email [sales@linkhamson.com](mailto:sales@linkhamson.com)