

SUPERFORM/A



SUPERFORM/A is a machine made for cutting and bending axial taped components, it is extremely compact and sturdy and its main characteristic is to form components with wire diameter up to 1.4 mm
Its tracking wheels are adjustable independently to allow rapid setup at different forms.


Production rate:

up to 40000 pcs/hr

7915.030
7915.031
7915.180
7915.185

Motor unit for SUPERFORM, 220V - 50/60Hz
Motor unit for SUPERFORM, 110V - 50/60Hz
CS10 feeder for loose axial components
Tape reel holder arm BR6

	B		P		C		D		d			L
	min	max	min	max	min	max	min	max	min	max	max	
7915.100A standard model	4	13	6.5	60 (40*)	1.2	16			0.4	1.3	50	7915.100AR quick setting
7915.100D reinforced bending knives	5	13	10.5	60 (40*)	2.4	16			0.6	1.4	50	7915.100DR quick setting
7915.100F reduced cutting length reduced bending length	4	13	5	60 (40*)	0.8	10			0.4	0.8	50	7915.100FR quick setting
7915.100G like "F" + fixed pitch	4	10	5	-	0.5	4			0.4	0.6	3.5	



(*) maximum P dimension with quick setting

SUPERFORM/S

SUPERFORM/S is a machine made for cutting and bending axial taped components for surface mount assembly. This machine, extremely compact and sturdy, can form components with wire diameter up to 1mm.


Special preforming dimensions can be made upon request.

Production rate:

up to 40000 pcs/hr

7915.104
7915.030
7915.031
7915.180
7915.185

SUPERFORM/S
Motor unit for SUPERFORM, 220V - 50/60Hz
Motor unit for SUPERFORM, 110V - 50/60Hz
CS10 feeder for loose axial components
Tape reel holder arm BR6



	P	C	L	D	d	B	h
Min mm	12	1.5			0.4±0.8	2	2.5
Max mm	47	10	40	16	fix		

SUPERFORM/AP

SUPERFORM/AP is a machine made for cutting and bending axial taped components for vertical assembling, and shaping a little curl on each lead. The machine handles wire diameters ranging from 1 mm to 1.4mm.

By replacing the 2 "cutting/forming wheels" with 2 "only cutting wheels" (optional) it is possible to obtain an U-shape without curls.

Production rate:

up to 20000 pcs/hr

7915.030
7915.031
7915.180
7915.185

Motor unit for SUPERFORM, 220V - 50/60Hz
Motor unit for SUPERFORM, 110V - 50/60Hz
CS10 feeder for loose axial components
Tape reel holder arm BR6

	P		B		C		L	d		D	h		z
	min	max	min	max	min	max	max	min	max	max	min	max	fix
7915.102A standard model z=3.1	6.5	60	10	14	1.2	10	50	1	1.3	16	7	11	3.1
7915.102B reinforced bending knives z=3.1	10.2	60			2.4				1.4				3.1
7915.102C standard model z=3.9	6.5	60			1.2				1.3				3.9
7915.102D reinforced bending knives z=3.9	10.2	60			2.4				1.4				3.9
7915.102E standard model z=5	6.5	60			1.2				1.3				5
7915.102F reinforced bending knives z=5	10.2	60			2.4				1.4				5

